HBrinker Mechanical Seal

Engineered seals

Mechanical Seal HBP-D







Materials

- Seal face: Silicon carbide (Q12), Carbon
 (A)
- Secondary seals: FKM (V), EPDM (E), FFKM (K)
- Metal parts: CrNiMo steel (G), Grade 5A (4T), SMO 654 (4U)

Mechanical Seal HBP-D

Operating range

Temperature: $t = -20 \,^{\circ}\text{C} \dots +140 \,^{\circ}\text{C} \left(-4 \,^{\circ}\text{F} \dots +284 \,^{\circ}\text{F}\right) (180 \,^{\circ}\text{C} (356 \,^{\circ}\text{F}) \text{ with Kalrez}^{\otimes} \text{ elastomers})$

4 051 (050 001) 0 401 (4

Pressure: p1 ... 25 bar (363 PSI), p3 <12 bar (174 PSI)

Sliding velocity: vg ... 20 m/s (66 ft/s)

Stock content: <8 %

Non-flow operation:

Temperature: t = +5 °C ... +100 °C (+41 °F ... +212 °F)

Pressure: p1 max. 10 bar (145 PSI), p3 > p1

Sliding velocity: vg <10 m/s (33 ft/s)

- Integrated seal for Sulzer A pumps
- Dual seal, balanced
- Semi cartridge unit
- Independent of direction of rotation
- Double pressure balanced
- Internal barrier fluid circulation
- Static springs on both sides
- No dynamic O-Ring on shaft
- Rugged design
- Shrink-fitted seal faces
- Seal faces have a large clearance to the shaft
- Wear part cost minimized

Advantages

- Individually integrated to equipment for the best sealing result
- Straightforward and easy installation
- Static springs on both face sides reduces influence of misalignment
- No damage of the shaft by dynamically loaded O-Rings
- Extended service life due to rugged design
- No brittle parts in contact with torque transmission pins
- Seal faces protected by strong steel parts and a large radial clearance

Recommended applications

- Pulp and paper industry
- Chemical industry
- Clean, abrasive or corrosive liquids
- Stocks of various kind
- Applications where crystallization is a problem
- Sulzer Ahlstar A (MS11) centrifugal pumps


Telegram: +3197010281216 WhatsApp: +3197010281216 Email: Info@Hbrinker.com

HBrinker Mechanical Seal

Engineered seals

Mechanical Seal HBP-D





Item	Description
1	Seal face
5	Seat
13	Sleeve
16	Housing
18	Pin
37	Locking fixture
2,12,15,22,23,24,25	O-Ring
43	Plug
LP-D-UP	Dual seal



Telegram: +3197010281216 WhatsApp: +3197010281216 Email: Info@Hbrinker.com